

SPRAY Stone[®]

LIMESTONE PLASTER



Product Data Sheet

- Zero VOC / Low Odor
- Liquidized Limestone / Acrylic
- Applies with Texture Hopper, Texture Machine or Brush
- Extremely Durable / Mold Resistant
- Water Resistant / Vapor Permeable
- Use Over Previously Painted Walls, New Construction, Block or Concrete

Features

- Real Limestone Plaster
- Acrylic Fortified-Interior and Exterior Use
- Spray on with Texture Hopper or Graco[®] Texspray RTX 1500
- May also be troweled or brushed
- White base tint able to any alkali proof colorant
- Spray applied plaster finish at lower cost per foot due with greatly reduced labor time

General Properties

Spray-Stone[®] is a real limestone based plaster. It can vary from the look, feel and texture of real limestone, to granite like textures. Colorants and spray techniques will decide which look is achieved. **Spray-Stone** contains acrylic which assists in adhesion, initial hardness and also flexibility of the film. The plaster will continue to harden through carbonation over time.

Recommended For

Spray-Stone may be used on a variety of substrates including; primed drywall, existing painted drywall, block wall, stucco or concrete. The durability of the plaster will be only as sound as the substrate. New drywall of surfaces with uneven porosity should first primed with a high quality high PH resistant primer. For water color enhancement and repellency seal with **Spray-Stone Sealer[™]**.

Limitations

Exterior use should be limited to non fade inorganic pigments only. The **Spray-Stone** finish will be determined by the type of scatter coating, smoothing with trowels, as well as polishing by sanding. The plaster may be sanded with 100-200 grit random orbital or drywall screens within 2 days. The **Spray-Stone Sealer[™]** enriches, but will not dull the brightness and natural glow of the limestone plaster. Do not apply over unsound substrate.

CAUTION: SPRAY-STONE IS HIGHLY AKALI! ALWAYS WEAR APPROVED SAFETY GOOGLES AND GLOVES. FAILURE TO DO SO MAY CAUSE SEVERE EYE DAMAGE OR SKIN BURNS!

FOR SPRAY USE ONLY GRACO[®] TEXSPRAY SERIES RTX 1500. RTX 1500 HAS A UNIQUE ROTOFLEX PUMP WHICH WILL EASILY PUMP SPRAY-STONE. YOU WILL ALSO NEED THE ADDITIONAL FINE FINISH TIP FOR APPLYING SMOOTH BASE COAT.

Small Job



Large Job



Technical Data

Spray-Stone Plaster

Generic Type.....	Limestone Plaster (highly alkali- 12 ph)
Pigment Type.....	Alkali Proof Organic or Inorganic
Pigment Quantity	0-16 oz per 5 gallons
Volume Solids.....	65% by volume and weight
Coverage base coats	250-350 sq. ft. per 5 base coat
Coverage scatter coat.....	300-400 sq. ft. per 5 top coat
Recoat.....	When color lightens
Surface Temperature.....	50°-80° F
Flash Point.....	Non-Flammable
Tools/Hands Cleanup	Soap and Water
VOC.....	Zero VOC